























**A**

**B**

**C**


2000.669.G 1.		Main Plate
3305.363.CO 2.		Cannon pinion with driver B (Aig.1)
2030.028.CO 3.		Centre bridge Centre bridge held by 3 screws 4000.250.
4000.250 4.		Screw
3406.039 5.		Sliding attachment Sliding attachment held by 1 screw 4000.250.
2130.181.CO 6.		Combined maintaining plate Combined maintaining plate held by 1 screw 4000.250.
4000.250 7.		Screw
3016.028 8.		Lever for setting lever Lever for setting lever held by 1 screw 4000.249.
4000.249 9.		Screw
3016.027 10.		Stop lever Stop lever Position held by 1 screw 4000.249.
4000.249 11.		Screw
3622.044 12.		Stator
3715.105.RK 13.		Rotor
3147.060.CO 14.		Intermediate wheel
3122.070.CO 15.		Third wheel
3136.174.CO 16.		Centre second wheel (Aig.1)
3004.203.CO 17.		Seconde intermediate wheel
3136.182.CO 18.		Small second wheel
3136.173.CO 19.		Centre second wheel (Aig.1)


**D**

2020.170.G  
20.  **Train wheel bridge**  
Train wheel bridge held by 3 screws 4000.250.


4000.244  
21.  **Screws**

3603.080  
22.  **Battery insulator**

3601.120.G  
23.  **Battery clamp +**  
Battery clamp held by 1 screw 4000.248.

4000.248  
24.  **Screw**

3503.071  
25.  **Tube**


**E**


3612.196  
26.  **Electronic module**  
Electronic module held by 5 screws 4000.250.

4000.250  
27.  **Screw**

3603.081  
28.  **Spacer**

4000.244  
29.  **Screws**

3600.032.HGF  
30.  **Battery 381**


**F**


2000.669.G  
31.  **Main Plate**

3017.054.CO  
32.  **Setting lever**

3905.063  
33.  **Setting lever jumper (3 positions)**  
Setting lever jumper held by 1 screw 4000.282.

4000.282  
34.  **Screw**

3001.061.FI  
35.  **Sliding pinion**



**G**


3015.077  
36.  **Yoke (3 positions)**  
Tensioning the spring arm.

3004.200  
37.  **Corrector setting wheel**

3004.200  
38.  **Corrector setting wheel**


3015.078.CO  
39.  **Rocking bar (3 positions)**  
Tensioning the spring arm.


**H**


2130.194  
40.  **Setting mechanism cover**  
Setting mechanism cover held by 4 screws 4000.305.

4000.305  
41.  **Screws**

3000.194.CO  
42.  **Stem**

3004.204  
43.  **Intermediate setting wheel**


3007.079.CO  
44.  **Minute wheel**





2130.185  
45.  **Minute train bridge**  
Minute train bridge held by 1 screw 4000.278.


4000.278  
46.  **Screw**





3301.296.CO  
47.  **Hour wheel (Aig.1)**


3147.066.CO  
48.  **Date corrector setting wheel**








**I**

2000.671.G 49.		<b>Main plate retro</b> Main plate retro held by 4 screws 4000.248.
4000.248 50.		<b>Screw</b>
3004.220 51.		<b>Tens indicator driving wheel</b> The short tooth of the tens indicator driving wheel must point to the center of the movement.
3500.072 52.		<b>Tens jumper</b>


**J**




2130.187 53.		<b>Tens jumper maintaining plate</b> Tens jumper maintaining plate held by 2 screws 4000.279. Tensioning the spring arm.
4000.279 54.		<b>Screw</b>
3004.208.CO 55.		<b>Date indicator driving wheel</b>
3147.061 56.		<b>Intermediate date wheel</b>



**K**

2130.188 57.		<b>Date indicator plate</b>
3905.068 58.		<b>Date corrector spring</b> Date corrector spring held by 1 screw 4000.244.
3905.066 59.		<b>Day rack lever spring</b> Tensioning the spring arm.
3500.069 60.		<b>Day jumper</b> Tensioning the spring arm.
3500.068 61.		<b>Date jumper</b>
3504.229.AF.1.A 62.		<b>Units indicator (standard)</b> Nick of the indicator at 3 o'clock.






L

2130.189 63.		<b>Date indicator maintaining plate</b> Date indicator maintaining plate held by 1 screw 4000.250.
4000.250 64.		<b>Screw</b>
3905.064 65.		<b>Date jumper spring</b> Insert the date jumper spring in the provided opening.



M


3147.062 66.		<b>Tens intermediate wheel</b> Arrow positioning radially outwards.
3315.003 67.		<b>Friction spring</b>
3504.230.AF.1.A 68.		<b>Tens indicator (standard)</b> Nick of the indicator at 3 o'clock.

2130.190.G 69.		<b>Date mechanism maintaining plate (12h)</b> Date mechanism maintaining plate held by 3 screws 4000.320.
-------------------	------------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------

4000.320 70.		<b>Screw</b>
-----------------	-------------------------------------------------------------------------------------	--------------

3506.077.G 71.		<b>Intermediate dial support</b> Polished version first.
-------------------	-------------------------------------------------------------------------------------	-------------------------------------------------------------

3506.076.G 72.		<b>Dial support</b>
-------------------	-------------------------------------------------------------------------------------	---------------------




N

8200 73.		<b>Moebius 8200</b>
-------------	-------------------------------------------------------------------------------------	---------------------


9014 74.		<b>Moebius 9014</b>
-------------	-------------------------------------------------------------------------------------	---------------------

124 75.		<b>Jismaa 124</b>
------------	-------------------------------------------------------------------------------------	-------------------

9020 76.		<b>Moebius 9020</b>
-------------	-------------------------------------------------------------------------------------	---------------------




Battery	<b>381</b>
Voltage	<b>1.55V</b>


**III**

*Setting stem in position III,  
60s measuring interval:*

Typical consumption	<b>0.1 <math>\mu</math>A</b>
Maximal consumption	<b>0.3 <math>\mu</math>A</b>


**I**

*Stem in position I, date  
mechanism not in gear:*

Typical consumption	<b>1.43 <math>\mu</math>A</b>
Maximal consumption	<b>3.1 <math>\mu</math>A</b>

*60s measuring time:*

Instantaneous rate **-10s/mth .. +20s/mth**

Lower working voltage limit	<b>1.20 V</b>
-----------------------------	---------------