

Caliber 502 – 10½"



Product Specifications

Analog quartz movement

Line	powertech
Caliber	502
Size	10½"
Version Swiss Made	1 Jewels / nickel plated
Version Swiss Parts	1 Jewels / nickel plated
Standard battery life	45 months
Standard hand fitting height	1

Functions

- 2 hands

Features

- Repairable metal watch movement
- Power saving mechanism with pulled out stem:
Reduction of consumption approximately 70%
- Interchangeability: All versions 10½" with same
movement height 3.00 mm and stem height 1.50 mm
- Very powerful stepping motor

Quartz Movements

Classic Functions

RONDA powertech

Caliber 502 – 10½"

Technical Specifications

Diameter Total	23.90 mm
Case fitting	23.30 mm
Movement height	3.00 mm
Height over standard battery	3.25 mm
Movement rest	0.80 mm
Height over stem	1.50 mm
Length of stem travel	0.45 mm
Stem thread	0.90 mm
Useful torque minute – typical	550 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Battery Specifications

Standard battery	No. 371
Standard battery life	45 months
Battery voltage	1.5 V
Current consumption – typical	1.28 µA
Current consumption – maximum	1.85 µA

Watch production

Drawing Casing ring (standard, PDF)
 Drawing Dial (stem 3h, PDF)
 Drawing Hand fitting (hand height 1-2, PDF)
 Drawing Stem

Watch repairs

Technical instruction (PDF)