

## Caliber Z60 – 13¼"



### Product Specifications

Analog quartz movement

Line startech

Caliber Z60

Size 13¼"

Version Swiss Made 0 Jewels / nickel plated

Version Swiss Parts 0 Jewels / nickel plated

Standard battery life 50 months

Standard hand fitting height 1

### Features

- Repairable movement with metal main plate and bridges
- Power saving mechanism with pulled out stem: Reduction of consumption approximately 70%
- Very easy handling by two pushers

### Functions

- 30 minute counter
- Center stop second (1/1 sec)
- ADD and SPLIT functions
- Chronograph
- Day indicator
- Small second
- Date

# Quartz Movements

## Chronographs

### RONDA startech

## Caliber Z60 – 13¼"

### Technical Specifications

|  |                   |
|--|-------------------|
| Diameter Total                             | 30.60 mm          |
| Case fitting                               | 30.00 mm          |
| Movement height                            | 4.60 mm           |
| Height over standard battery               | 4.60 mm           |
| Movement rest                              | 1.37 mm           |
| Height over stem                           | 1.75 mm           |
| Length of stem travel                      | 1.00 mm           |
| Stem thread                                | 0.90 mm           |
| Useful torque second – typical             | 6 µNm             |
| Useful torque minute – typical             | 300 µNm           |
| Useful torque center stop second – typical | 6 µNm             |
| Operating temperature                      | 0 - 50 °C         |
| Instantaneous rate                         | -10/+20 sec/month |
| Resistance to magnetic fields              | 18.8 Oe           |
| Resistance against shock                   | NIHS 91-10        |

### Battery Specifications

|                               |                                      |
|-------------------------------|--------------------------------------|
| Standard battery              | No. 395                              |
| Standard battery life         | 50 months                            |
| Battery voltage               | 1.5 V                                |
| Current consumption – typical | 1.42 µA (Date Mechanism not in Gear) |
| Current consumption – maximum | 3 µA (Date Mechanism not in Gear)    |



### Watch production

- Drawing Casing ring (standard, PDF)
- Drawing Dial (stem 3h, calendar 4h, PDF)
- Drawing Dial (stem 3h, calendar 4h - 6h - 8h, large date, PDF)
- Drawing Dial (stem 3h, calendar 12h, large date, PDF)
- Drawing Hand fitting (Zeigerwerkhöhe 1, PDF)
- Drawing Stem
- Casing information (PDF)

### User's manual

- User's manual (PDF)