


## Caliber 756 – 5½"



### Product Specifications

Analog quartz movement

Line	normtech
Caliber	756
Size	5½"
Version Swiss Made	4 Jewels / gold plated
Version Swiss Parts	1 Jewels / nickel plated
Standard battery life	7 Years
Standard hand fitting height	1

### Features

- Very long battery life
- Repairable metal watch movement
- Many high hand heights available
- Electronic Time Setting:<br>brief pressure up to two seconds - minute correction<br>medium pressure between two and four seconds - hour correction<br>Pressure more than four seconds - continuous correction until corrector is released

### Functions

- Electronic time setting
- 2 hands

## Caliber 756 – 5½"

### Technical Specifications

Diameter Total	13.00 mm
Case fitting	13.00 mm
Movement height	3.10 mm
Height over standard battery	3.10 mm
Movement rest	0.40 mm
Height over stem	0.00 mm
Length of stem travel	0.00 mm
Stem thread	0.00 mm
Useful torque minute – typical	30 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10 / +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

### Battery Specifications

Standard battery	No. 379
Standard battery life	7 Years
Battery voltage	1.5 V
Current consumption – typical	0.34 µA
Current consumption – maximum	0.4 µA

### Watch production

Drawing Casing ring (standard, PDF)  
Drawing Dial (Stem, PDF)  
Drawing Hand fitting (hand height 0-5, PDF)

### User's manual

User's manual (PDF)