


Caliber 753 – 5½"



Product Specifications

Analog quartz movement

Line normtech

Caliber 753

Size 5½"

Version Swiss Made 5 Jewels / gold plated EOL

Version Swiss Parts 1 Jewels / nickel plated

Standard battery life 27 months

High battery life 36 months

Standard hand fitting height 1

Features

- Repairable metal watch movement
- Power saving mechanism with pulled out stem:
Reduction of consumption approximately 70%
- Many high hand heights available

Functions

- 3 hands

Caliber 753 – 5½"

Technical Specifications

Diameter Total	13.00 mm
Case fitting	13.00 mm
Movement height	2.50 mm
Height over standard battery	2.65 mm
Height over high battery	3.25 mm
Movement rest	0.40 mm
Height over stem	1.00 mm
Length of stem travel	0.40 mm
Stem thread	0.90 mm
Useful torque second – typical	5 µNm
Useful torque minute – typical	250 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Battery Specifications

Standard battery	No. 379
High battery	No. 319
Standard battery life	27 months
High battery life	36 months
Battery voltage	1.5 V
Current consumption – typical	0.76 µA
Current consumption – maximum	1.1 µA

Watch production

Drawing Casing ring (standard, PDF)
Drawing Casing ring (high battery, PDF)
Drawing Dial (stem 3h, PDF)
Drawing Hand fitting (hand height 0-6, A, PDF)
Drawing Stem

Watch repairs

Technical instruction (PDF)