

Quartz Movements

Classic Functions

RONDA slimtech

Caliber 1032 – 3¾ x 6'''



Product Specifications

Analog quartz movement

Line	slimtech
Caliber	1032
Size	3¾ x 6'''
Version Swiss Made	7 Jewels / gold plated
Version Swiss Parts	7 Jewels / nickel plated
Standard battery life	60 months
Standard hand fitting height	1

Features

- Do not pull stem during storage
- Very long battery life
- Repairable metal watch movement

Functions

- 2 hands

Quartz Movements

Classic Functions

RONDA slimtech

Caliber 1032 – 3¾ x 6"

Technical Specifications

Diameter Total	9.00 mm
Case fitting	9.00 mm
Movement height	1.95 mm
Height over standard battery	2.10 mm
Movement rest	0.20 mm
Height over stem	0.62 mm
Length of stem travel	0.30 mm
Stem thread	0.70 mm
Useful torque minute – typical	21 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Battery Specifications

Standard battery	No. 317
Standard battery life	60 months
Battery voltage	1.5 V
Current consumption – typical	0.25 µA
Current consumption – maximum	0.3 µA

Watch production

Drawing Casing ring (standard, PDF)
 Drawing Dial (stem 3h, PDF)
 Drawing Hand fitting (hand height 0-3, PDF)
 Drawing Stem

Watch repairs

Technical instruction (PDF)