User's Manual English Movements Caliber



RONDA xtratech

- 6203.B

- 7003.L

- 7003.N

- 7004.N

- 7004.P

You have decided to buy a watch, which was assembled by a watchmaker using a Ronda movement. Please note that no watches are produced or distributed under the Ronda brand

In case of repairs, guarantee claims and guestions concerning the functioning of a watch, purchasers and consumers should contact their retailer or the watch manufacturer, for which the relevant information can be found in the sales or quarantee documentation provided with the watch.

Crown A

Position of rest (watch running)

Quick-change correction for date The date can also be corrected during the day-changing

phase between 10.00 pm and midnight. The date of the following day has to be set, because no automatic date change takes place at midnight.

- Pull the crown out to position II (watch still running).
- Turn the crown clockwise until the required date
- appears. Push the crown back into position I.

- Pos. III Setting the time (both time zones together)

 - Pull the crown out to position III (watch stopped). Turn the crown, until the current time is displayed
 - (remember the 24-hour cycle). - Push the crown back into position I.

Cal. 7003.L

 \rightarrow



Cal. 7004.P

Crown B

Position of rest

Setting the time of the 2nd time zone

During the time setting of the 2nd time zone. crown A must be in position I.

- Pull the crown out to position II.
- Turn the crown, until the desired time is displayed.

Cal. 6203.B

Push the crown back into position I.

Cal. 7004.N Position of rest (watch running)

Quick-change correction for date

The date can also be changed during the day-changing phase between approx. 8.00 pm and midnight. The date of the following day has to be set, because no automatic date change takes place at midnight.

- Pull the crown out to position II (watch still running).
- Turn the crown until the current date appears. - Push the crown back into position I.

Pos. III Setting the time

Pull the crown out to position III (watch stopped).

Cal. 7003.L / 7003.N / 7004.N / 7004.P

- Turn the crown, until the current time is displayed (remember the 24-hour cycle).
- Push the crown back into position I.

Setting the day of the week

There is no quick-change correction available for setting the day of the week.

- Pull the crown out to position III (watch stopped).
- Turn the hands forward by turning the crown, until
- the current day of the week appears. Push the crown back into position II and set the current
- date using the guick change correction. - Push the crown back into position I.

Battery type: 373/SR916SW Cal. 7003.L / 7003.N / 7004.N / 7004.P Battery type: 381/SR1120SW

Precision: +20/-10 seconds per month



Cal. 6203 B



08/2023