

## Caliber 702 – 10½"



### Product Specifications

Analog quartz movement

Line	normtech
Caliber	702
Size	10½"
Version Swiss Made	5 Jewels / gold plated
Version Swiss Parts	1 Jewels / nickel plated
Standard battery life	60 months
Standard hand fitting height	1

### Features

- Very long battery life
- Repairable metal watch movement
- Power saving mechanism with pulled out stem:  
Reduction of consumption approximately 70%

### Functions

- 2 hands

## Caliber 702 – 10½"

### Technical Specifications

Diameter Total	23.90 mm
Case fitting	23.30 mm
Movement height	2.50 mm
Height over standard battery	2.75 mm
Movement rest	0.30 mm
Height over stem	1.00 mm
Length of stem travel	0.50 mm
Stem thread	0.90 mm
Useful torque minute – typical	400 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

### Battery Specifications

Standard battery	No. 371
Standard battery life	60 months
Battery voltage	1.5 V
Current consumption – typical	0.96 µA
Current consumption – maximum	1.35 µA

### Watch production

Drawing Casing ring (standard, PDF)  
Drawing Dial (stem 3h, PDF)  
Drawing Hand fitting (hand height 0-3, 6, PDF)  
Drawing Stem

### Watch repairs

Technical instruction (PDF)