

Caliber 714 – 11½"



Product Specifications

Analog quartz movement

Line normtech

Caliber 714

Size 11½"

Version Swiss Made 5 Jewels / gold plated

Version Swiss Parts 1 Jewels / nickel plated

Standard battery life 60 months

Standard hand fitting height 1

Features

- Very long battery life
- Repairable metal watch movement
- Power saving mechanism with pulled out stem:
Reduction of consumption approximately 70%

Functions

- Date
- 2 hands

Caliber 714 – 11½"

Technical Specifications

| | |
|--------------------------------|--------------------|
| Diameter Total | 26.00 mm |
| Case fitting | 25.60 mm |
| Movement height | 2.50 mm |
| Height over standard battery | 2.75 mm |
| Movement rest | 0.60 mm |
| Height over stem | 1.00 mm |
| Length of stem travel | 0.90 mm |
| Stem thread | 0.90 mm |
| Useful torque minute – typical | 400 µNm |
| Operating temperature | 0-50 °C |
| Instantaneous rate | -10/ +20 sec/month |
| Resistance to magnetic fields | 18.8 Oe |
| Resistance against shock | NIHS 91-10 |

Battery Specifications

| | |
|-------------------------------|---|
| Standard battery | No. 371 |
| Standard battery life | 60 months |
| Battery voltage | 1.5 V |
| Current consumption – typical | 0.96 µA (Date Mechanism not in Gear) |
| Current consumption – maximum | 1.35 µA (Date Mechanism not in Gear) |

Watch production

Drawing Casing ring (standard, PDF)
Drawing Dial (stem 3h, calendar 4h, PDF)
Drawing Dial (stem 3h, calendar 3h, PDF)
Drawing Dial (stem 3h, calendar 6h, PDF)
Drawing Dial (stem 3h, calendar 3h, round, PDF)
Drawing Dial (stem 3h, calendar 6h, round, PDF)
Drawing Dial (stem 3h, calendar 4 1/2 h, PDF)
Drawing Dial (stem 3h, calendar 4h, round, PDF)
Drawing Hand fitting (hand height 1-3, PDF)
Drawing Stem

User's manual

User's manual (PDF)

Watch repairs

Technical instruction (PDF)