

## Caliber 1003 – 10½"



### Product Specifications

Analog quartz movement

Line	slimtech
Caliber	1003
Size	10½"
Version Swiss Made	8 Jewels / gold plated EOL
Standard battery life	25 months
High battery life	40 months
Standard hand fitting height	1

### Functions

- 3 hands

### Features

- Repairable metal watch movement
- Power saving mechanism with pulled out stem:  
Reduction of consumption approximately 70%
- Complete interchangeability between 1002-1009,  
1012-1019

## Caliber 1003 – 10½"

### Technical Specifications

Diameter Total	23.90 mm
Case fitting	23.30 mm
Movement height	1.90 mm
Height over standard battery	1.90 mm
Height over high battery	2.15 mm
Movement rest	0.35 mm
Height over stem	0.75 mm
Length of stem travel	1.00 mm
Stem thread	0.90 mm
Useful torque second – typical	4 µNm
Useful torque minute – typical	200 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

### Battery Specifications

Standard battery	No. 341
High battery	No. 315
Standard battery life	25 months
High battery life	40 months
Battery voltage	1.5 V
Current consumption – typical	0.74 µA
Current consumption – maximum	1.1 µA

### Watch production

Drawing Casing ring (high battery, PDF)  
Drawing Casing ring (standard, PDF)  
Drawing Dial (stem 3h, PDF)  
Drawing Hand fitting (hand height 0-2, PDF)  
Drawing Stem

### Watch repairs

Technical instruction (PDF)