

Quartz Movements

Classic Functions

RONDA slimtech

Caliber 1032 – 3¾ x 6'''



Product Specifications

Analog quartz movement

| | |
|------------------------------|--------------------------|
| Line | slimtech |
| Caliber | 1032 |
| Size | 3¾ x 6''' |
| Version Swiss Made | 7 Jewels / gold plated |
| Version Swiss Parts | 7 Jewels / nickel plated |
| Standard battery life | 60 months |
| Standard hand fitting height | 1 |

Features

- Do not pull stem during storage
- Very long battery life
- Repairable metal watch movement

Functions

- 2 hands

Quartz Movements

Classic Functions

RONDA slimtech

Caliber 1032 – 3¾ x 6"

Technical Specifications

| | |
|--------------------------------|--------------------|
| Diameter Total | 9.00 mm |
| Case fitting | 9.00 mm |
| Movement height | 1.95 mm |
| Height over standard battery | 2.10 mm |
| Movement rest | 0.20 mm |
| Height over stem | 0.62 mm |
| Length of stem travel | 0.30 mm |
| Stem thread | 0.70 mm |
| Useful torque minute – typical | 21 µNm |
| Operating temperature | 0 - 50 °C |
| Instantaneous rate | -10/ +20 sec/month |
| Resistance to magnetic fields | 18.8 Oe |
| Resistance against shock | NIHS 91-10 |

Battery Specifications

| | |
|-------------------------------|-----------|
| Standard battery | No. 317 |
| Standard battery life | 60 months |
| Battery voltage | 1.5 V |
| Current consumption – typical | 0.25 µA |
| Current consumption – maximum | 0.3 µA |

Watch production

Drawing Casing ring (standard, PDF)
 Drawing Dial (stem 3h, PDF)
 Drawing Hand fitting (hand height 0-3, PDF)
 Drawing Stem

Watch repairs

Technical instruction (PDF)