

## Caliber 1042 – 4¼"



### Product Specifications

Analog quartz movement

Line	slimtech
Caliber	1042
Size	4¼"
Version Swiss Made	5 Jewels / gold plated
Version Swiss Parts	5 Jewels / nickel plated
Standard battery life	36 months
Standard hand fitting height	1

### Features

- Repairable metal watch movement
- Do not pull stem during storage

### Functions

- 2 hands

# Quartz Movements

## Classic Functions

### RONDA slimtech

## Caliber 1042 – 4¼"

### Technical Specifications

Diameter Total	10.40 mm
Case fitting	10.00 mm
Movement height	2.90 mm
Height over standard battery	2.90 mm
Movement rest	0.30 mm
Height over stem	0.55 mm
Length of stem travel	0.33 mm
Stem thread	0.70 mm
Useful torque minute – typical	14 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

### Battery Specifications

Standard battery	No. 335
Standard battery life	36 months
Battery voltage	1.5 V
Current consumption – typical	0.23 µA
Current consumption – maximum	0.3 µA

### Watch production

Drawing Casing ring (standard, PDF)  
 Drawing Casing ring (standard, PDF)  
 Drawing Dial (stem 3h, PDF)  
 Drawing Hand fitting (hand height 0-1, PDF)  
 Drawing Stem

### Watch repairs

Technical instruction (PDF)