



Caliber 7004.B – 15'''



Product Specifications

Analog quartz movement

Line xtratech

Caliber 7004.B

Size 15'''

Version Swiss Made 6 Jewels / gold plated EOL

Standard battery life 48 months

Standard hand fitting height 1

Features

- Repairable metal watch movement
- Power saving mechanism with pulled out stem:
Reduction of consumption approximately 70%
- Big date with quick change

Functions

- Multifunction
- Big date
- Small second
- 2 hands

Quartz Movements

Multifunctions

RONDA xtratech

Caliber 7004.B – 15"

Technical Specifications

Diameter Total	34.60 mm
Case fitting	33.80 mm
Movement height	5.60 mm
Height over standard battery	5.60 mm
Movement rest	0.60 mm
Height over stem	3.30 mm
Length of stem travel	1.00 mm
Stem thread	0.90 mm
Useful torque second – typical	10 µNm
Useful torque minute – typical	500 µNm
Operating temperature	0 - 50 °C
Instantaneous rate	-10/ +20 sec/month
Resistance to magnetic fields	18.8 Oe
Resistance against shock	NIHS 91-10

Battery Specifications

Standard battery	No. 381
Standard battery life	48 months
Battery voltage	1.5 V
Current consumption – typical	1.43 µA (Date Mechanism not in Gear)
Current consumption – maximum	3.1 µA (Date Mechanism not in Gear)



Watch production

Drawing Casing ring (standard, PDF)
 Drawing Dial (stem 3h, calendar 12h, PDF)
 Drawing Hand fitting (hand height 1, PDF)
 Drawing Stem
 Casing information (PDF)

User's manual

User's manual (PDF)

Watch repairs

Technical instruction up to code M (PDF)
 Technical instruction as of code N (PDF)